



Shock Wave Interactions

A CFD Study of CUBRC LENS-XX Laminar Experiments

Dinesh K. Prabhu
ERC, Inc.

June 20, 2014

AIAA Aviation and Aeronautics Forum and Exposition (AVIATION 2014)

Tech. Session FD-33. Comparison between CFD and Measurements in Hypervelocity Airflows Part 1: Real-gas Effects on Laminar Shockwave Boundary Layer Interaction



Acknowledgments

Entry Systems and Technology Division

- **Michael Holden and Matthew MacLean of CUBRC for the kind invitation**
- **Michael Wright and Michael Barnhardt of NASA Ames Research Center for encouragement of the work through NASA's ESM (formerly HEDL) program**
- **Michael Olsen, Michael Barnhardt and David Saunders for thorough review of the laminar flow manuscript**
- **NASA Ames Research Center for funding this work via Contract NNA10DE12C to ERC, Inc.**



Objectives

Entry Systems and Technology Division

Primary

To predict surface distributions of pressure and heat flux using “standard” simulation model(s) for:

(a) Sharp $25^\circ / 55^\circ$ double cone model

(b) Hollow cylinder-flare (30°) model

tested at laminar flow conditions in LENS-XX at CUBRC

Secondary


To understand/quantify sensitivity of predictions to uncertainties in freestream conditions

To understand/quantify the influence of physical models (thermochemical vs. chemical nonequilibrium) on flow predictions

Focus of this presentation is solely on the double cone model

Double Cone Model

Entry Systems and Technology Division



Cone-flare model has a sharp tip

Same model has been tested in LENS-I (reflected shock tunnel)



Modeling and Simulation

Entry Systems and Technology Division

Simulation Tool

- v4.03.1 of *Dplr* (axisymmetric)

Physics

- 5-species air (N_2 , O_2 , NO , N , O) for all cases
- 2 Physical models
 - Thermochemical nonequilibrium – TCNEQ
 - Chemical nonequilibrium - TEQ
- Thermodynamic properties of species: Lewis curve fits
 - For consistency with Cheetah
 - Typically would have used SHO/RR
- Momentum and energy transport properties: Gupta-Yos curve fits
- Mass transport: Self-consistent effective binary diffusion
- Chemistry: Park 90 mechanism and kinetics
- Wall model: Fully catalytic to atom recombination and $T_w = 300$ K

Numerics

- 1st-order accuracy in time and 2nd-order accuracy in space

Grid tailoring capability of *DPLR* exercised in all computations



Strategy

Entry Systems and Technology Division

- Establish grid requirements via the following studies:
 - **Wall-normal grid resolution**
 - Cell Reynolds number used the criterion
 - Final cell Re used is 0.1
 - **Wall temperature sensitivity**
 - Heating results insensitive to choice of wall temperature for high total enthalpy cases
 - At lowest total enthalpy, less than 1% change for wall temperatures between 400 and 300 K
 - **Grid convergence** established by computing on grids that are 4x coarser and finer than nominal grid
 - Results reported on nominal grid only
 - **2nd-order spatial accuracy** found to be adequate for all axisymmetric computations
 - Some sensitivity seen in 3D computations, but 3D grids employed were coarser than nominal axisymmetric grid



Freestream Velocity Uncertainty Line of Inquiry, I

Entry Systems and Technology Division

- **Surface heating is proportional to the “enthalpy potential”**
 - $q \propto H_0 - h_w$
- **Total enthalpy is a conserved quantity across a normal shock**
 - Inviscid flow is adiabatic
- **Total enthalpy is a sum of flow kinetic energy and thermochemical enthalpy**

$$H_0(T, T_v) = \frac{1}{2} V^2 + \sum_{s=\text{molecules}} c_s \left\{ R_s T \left[3.5 + \left(\frac{Q_{v,s}}{T} \right) \frac{\exp(-Q_{v,s}/T_v)}{1 - \exp(-Q_{v,s}/T_v)} \right] + D_f H_s^0 \right\} + \sum_{s=\text{atoms}} c_s [2.5 R_s T + D_f H_s^0]$$

- If freestream is undissociated air, then no atomic contribution

$$H_0(T_\infty, T_{v,\infty}) = \frac{1}{2} V_\infty^2 + \sum_{s=N_2, O_2} c_{s,\infty} \left\{ R_s T_\infty \left[3.5 + \left(\frac{Q_{v,s}}{T_\infty} \right) \frac{\exp(-Q_{v,s}/T_{v,\infty})}{1 - \exp(-Q_{v,s}/T_{v,\infty})} \right] + D_f H_s^0 \right\}$$

Freestream kinetic energy is the dominant component – Velocity is the sensitivity variable



Freestream Velocity Uncertainty Line of Inquiry, II

Entry Systems and Technology Division

- Pitot pressure can be measured reasonably well – $P_0 \approx \rho_\infty V_\infty^2$
 - Cannot break this product without an independent measurement of velocity
- Assume uncertainty in given freestream velocity is $\pm x\%$, but P_0 is fixed

$$V_{\infty}^{new} = f V_{\infty}^{old} \quad f = 1 \pm x$$

- Therefore,

$$P_0^{new} = P_0^{old} \quad \Rightarrow \quad r_{\infty}^{new} (V_{\infty}^{new})^2 = r_{\infty}^{old} (V_{\infty}^{old})^2 \quad \Rightarrow \quad r_{\infty}^{new} = \frac{1}{f^2} r_{\infty}^{old}$$

- Still have to specify T_∞
 - One way is to assume static pressure is also fixed (at nom.)

$$p_{\infty}^{new} = p_{\infty}^{old} \quad \Rightarrow \quad r_{\infty}^{new} \frac{\gamma}{\gamma-1} \frac{a_{\infty}^2}{c_{s,\infty}^2} R_s T_{\infty}^{new} = r_{\infty}^{old} R T_{\infty}^{old} \quad \Rightarrow \quad T_{\infty}^{new} = f^2 T_{\infty}^{old}$$

Freestream enthalpy will change! => Freestream velocity and total enthalpy are synonymous

$$H_0(T_{\infty}^{new}) = f^2 \left(\frac{1}{2} (V_{\infty}^{old})^2 + 3.5 R T_{\infty}^{old} \right) = f^2 H_0(T_{\infty}^{old})$$



Learning Cases – Cases from **LENS-I** Matrix

(“Open” Validation Cases in AIAA 2013-2836)

Entry Systems and Technology Division

	Run 90	Run 91	Run 80	Run 42
$\rho_{\infty}/\text{g.m}^{-3}$	1.8342	1.5498	1.291	1.34
$V_{\infty}/\text{km.s}^{-1}$	2.731	4.148	3.067	4.063
T_{∞}/K	190.1	729	166	303
$T_{v\infty}/\text{K}$	1001	773.1	2711	3085
Gas comp. (mass fractions)	O ₂ = 0.9986 O = 0.0014	O ₂ = 0.9389 O = 0.0611	N ₂ = 0.9999 N = 0.0001	N ₂ = 0.9973 N = 0.0027
$H_0/\text{MJ.kg}^{-1}$	3.99	10.26	5.28	9.17
Molecular (tr/rot)	4.3%	6.1%	3.3%	3.4%
Molecular(vib/el)	1.7%	0.3%	7.6%	5.5%
Atomic	0.5%	9.7%	0.1%	1.0%
Kin.energy	93.5%	83.9%	89.0%	90.1%

Freestream conditions from numerical simulations of nozzle flow


Double cone configuration has been extensively studied by Nompelis *et al.* (AIAA 2010-1283)

Unable to obtain a stable solution for Run 80 with TCNEQ model, but TEQ model is stable


Learning Case – Run 90 (O₂/O Mixture)

Entry Systems and Technology Division

Pressure



Heat Flux



Predicted environments relatively insensitive to choice of TCNEQ or TEQ


Velocity has a bigger impact – lower velocity larger bubble size

Velocity influence on the 55° cone is also large


Learning Case – Run 90 (O₂/O Mixture)

Entry Systems and Technology Division

Pressure



Heat Flux




If velocity is 95% of nominal, then better replication of pressure data
Error bars on experimental data not provided


Learning Case – Run 91 (O₂/O Mixture)

Entry Systems and Technology Division

Pressure



Heat Flux




If velocity is 90% of nominal, then better replication of pressure data

The double peak characteristic post-impingement needs schlieren image for confirmation


Learning Case – Run 91 (O₂/O Mixture)

Entry Systems and Technology Division

Nominal Velocity



90% Nominal Velocity



Velocity magnitude determines whether or not there is a Mach stem
A schlieren image for this case would be most helpful



From “Open” to “Blind” Validation Cases

Entry Systems and Technology Division

- **“Open” validation cases are from LENS-I**
 - LENS-I is a reflected shock tunnel
- **“Blind” validation cases are from LENS-XX**
 - LENS-XX is an expansion tunnel

Still retain the freestream velocity uncertainty line of inquiry



“Blind” Validation Cases – LENS-XX Matrix

Entry Systems and Technology Division

	Case 1	Case 2	Case 6	Case 5	Case 3	Case 4
$\rho_{\infty}/\text{g.m}^{-3}$	0.499	0.984	2.045	1.057	0.51	0.964
$V_{\infty}/\text{km.s}^{-1}$	3.246	4.303	5.466	5.996	6.028	6.497
T_{∞}/K	175	389	573	523	521	652
P_0/kPa	5.1	17.5	59	36.8	18	39.5
$H_0/\text{MJ.kg}^{-1}$	5.44	9.65	15.23	18.51	18.7	21.77
Thermal	3.2%	4.1%	3.7%	2.8%	2.8%	3.0%
Kin.energy	96.8%	95.9%	96.3%	97.2%	97.2%	97.0%
M_{∞}	12.2	10.9	11.46	13.14	13.23	12.82
$Re_{u_{\infty}} \times 10^{-6}/\text{m}^{-1}$	0.14	0.19	0.39	0.23	0.11	0.2
$\lambda_{\infty}/\text{mm}$	0.129	0.085	0.043	0.084	0.178	0.095
$Kn_{\infty} \times 10^3$	1.40	0.92	0.47	0.91	1.93	1.03


Freestream conditions from *CHEETAh* code (0D/Equilibrium)
Code calibrated to shock velocity and pressure measurements

Blind Study – Case 1 (Low Enthalpy)


Influence of Freestream Velocity

Entry Systems and Technology Division

Pressure



Heat Flux



The test configuration is shown in light grey lines

T_∞ from “keep M fixed” or “keep Re fixed” idea has little influence on predictions

$\pm 10\%$ variation in velocity at low enthalpy (5 MJ/kg) has more influence




Blind Study – Case 4 (High Enthalpy)


Influence of Freestream Velocity

Entry Systems and Technology Division

Pressure



Heat Flux



T_{∞} from “keep M fixed” or “keep Re fixed” idea has little influence on predictions
 $\pm 10\%$ variation in velocity at high enthalpy (21.8 MJ/kg) has more influence


Blind Study – Cases 1 & 4

Influence of Angle of Attack


Entry Systems and Technology Division

Low Enthalpy
(Case 1)

$\alpha = 0^\circ$




$\alpha = 2^\circ$




$q/W.cm^{-2}$ 0 15 30 45 60 75 90 105 120 135 150

High Enthalpy
(Case 4)

$\alpha = 0^\circ$



$\alpha = 2^\circ$



$q/W.cm^{-2}$ 0 200 400 600 800 1000 1200 1400 1600 1800 2000

Angle of attack influence is greatest for largest separation bubble size


Bubble size at 5 MJ/kg >> Bubble size at 21.8 MJ/kg

Blind Study – Case 1 (Low Enthalpy)


Influence of Gas Model

Entry Systems and Technology Division

Pressure



Heat Flux



SHO/RR or LeRC fits for thermodynamic properties makes no difference
Thermal relaxation at low enthalpy (5 MJ/kg) has an enormous influence




Blind Study – Case 4 (High Enthalpy)


Influence of Gas Model

Entry Systems and Technology Division

Pressure



Heat Flux



SHO/RR or LeRC fits for thermodynamic properties makes no difference

Thermal relaxation at high enthalpy (21.8 MJ/kg) has smaller influence than in Case 1



Concluding Remarks

Entry Systems and Technology Division

- **Accomplishments**
 - All cases computed for both configurations
 - The hollow cylinder-flare configuration has not received the same level of attention as the double cone configuration
 - Each case had something unique to offer, especially Case 2
 - Schlieren images for these cases would be most helpful
- **Things still left to do**
 - Study influence of transport properties
 - Complete grid convergence studies for the hollow cylinder-flare configuration
- **Lesson Learned and/or Open issues (in the view of the author)**
 - Since freestream velocity has the most influence on environments, would be preferable to have independent measurements of freestream velocity
 - Would also be preferable to work with the actual nozzle contour and perform 3D flow computations -> predicted freestream chemical state is a bonus
 - Need some cases from facility characterization as well to complete V&V story
 - Stag. measurements of heat flux *and* pitot pressure for either the 3.5-in cylinder or 1.25-in hemisphere